


TOYOTOMI

Toyotomi Model Name	TAD-T33
	
Duct	Double
UL certified	Yes
Maximum cooling capacity per Ashrae 128	11,500BTU
Maximum cooling capacity per DOE	7,100 sacc
CEER compliant product	Yes, 7.2
Rated voltage/Frequency (V~Hz)	115V/ 60Hz
Cooling maximum Input Power	1000w
Refrigerant	R32
Timer	24h count-down
Fan speed	3
Setting temperature (cooling)	61-89 °F
Usage ambient temperature (cooling)	64-95°F
Water storage capacity	no water tank
Unit dimension (W x D x H) mm	460 x 385 x 746 mm
Unit dimension (W x D x H) inc.	18.4 x 15.2 x 29.4 inc.
carton dimension (W*D*H) mm	505 x 462 x 870mm
carton dimension (W*D*H) inc.	19.9 x 18.2 x 34.3 inc.
carton dimension w/ sleeve (W" x D" x H")	21.5 x 20 x 35
carton dimension (W x D x Hmm)	19.9 x 18.1 x 34.3
Net Weight (KG/Lb)	28.9/63.7 (KG/Lb)
Gross Weight (KG/Lb)	35.1/77.4 (KG/Lb)
Container loading Qty: 20'ft	110
40'ft	230
40'HQ	345
Exhaust Duct Hose Diameter	dia. 150 x 1220mm
Air Intake Duct Hose Diameter (if double duct unit)	dia. 130 x 1220mm

